

# BUTTON FERRULE SW-705

Excellent as drum attachment devices, our TUF-GRIP Button Ferrules develop the minimum breaking force of wire rope. You can apply them at any position along an assembly to serve many functions – as stops or pullers, for example.

The standard button material is carbon steel, but can be ordered as stainless steel if desired. Measure the length using maximum dimensions (from outside end of the ferrule).

## Dimensions for Button Ferrule

Dash no.	Rope dia.	A <sub>S</sub>	Approx. B <sub>S</sub>	Dash no.	Rope dia.	A <sub>S</sub>	Approx. B <sub>S</sub>
3	3/32	5/16	1/2	16	1/2	1 1/8	2 3/8
4	1/8	3/8	5/8	18	9/16	1 1/4	2 5/8
5	5/32	7/16	3/4	20	5/8	1 3/8	2 7/8
6	3/16	1/2	7/8	24	3/4	1 9/16	3 1/2
7	7/32	9/16	1	28	7/8	1 3/4	4 1/8
8	1/4	5/8	1 1/8	32	1	2	4 3/4
9	9/32	11/16	1 3/8	36	1 1/8	2 1/4	5 1/4
10	5/16	3/4	1 1/2	40	1 1/4	2 1/2	5 7/8
12	3/8	7/8	1 3/4	44	1 3/8	2 3/4	6 1/2
14	7/16	1	2	48	1 1/2	3	7 1/8

All dimensions are in inches.

You can specify a custom design with a different button length or finish diameter, but please send a sketch of the assembly when you order. Keep in mind that this may reduce the assembly's rated capacity. For proven advice, contact our **Customer Service Department**.

EQUIVALENT TO SA157 SERIES

