

# JAW SW-704

You can use the TUF-GRIP SW-704 Jaw two ways.

One, with the TUF-GRIP SW-703 Pin Eye when you need multiple lengths of assemblies. And two, for single lug attachment of a wire rope assembly.

Our Jaw offers excellent pin bearing surface for your applications. You can also depend on long life with its rugged, one-piece, drop-forged steel construction. Measure the length of the assembly from the center of the pin.

We supply the TUF-GRIP Jaw without a pin or a nut and bolt, but we'll provide either if you specify on your order.

EQUIVALENT TO SA152 SERIES

## Dimensions for Jaw

Dash No.	Rope Dia.	D	E	F	G	P	A <sub>s</sub>	Afterswage C <sub>s</sub>
3	3/32	5/8	9/32	13/32	5/8	1/4	7/32	1 15/16
4	1/8	5/8	9/32	13/32	5/8	1/4	7/32	2 1/4
5	5/32	7/8	9/32	15/32	11/16	1/4	1/4	2 13/16
6	3/16	7/8	5/16	1/2	13/16	5/16	5/16	3 1/8
7	7/32	1 1/16	13/32	5/8	1	3/8	7/16	3 3/4
8	1/4	1 1/16	13/32	5/8	1	3/8	7/16	4 1/16
9	9/32	1 5/16	1/2	3/4	1 5/16	1/2	9/16	4 3/4
10	5/16	1 5/16	1/2	3/4	1 5/16	1/2	9/16	5 1/16
12	3/8	1 1/2	9/16	15/16	1 5/8	5/8	5/8	6
14	7/16	1 3/4	11/16	1 1/8	1 7/8	3/4	3/4	7
16	1/2	2 1/16	25/32	1 3/16	2 1/8	7/8	7/8	8 1/16
18	9/16	2 1/16	25/32	1 3/16	2 1/8	7/8	7/8	8 5/8
20	5/8	2 13/16	1	1 3/4	2 5/8	1 1/8	1 1/8	10 3/8
24	3/4	2 13/16	1 1/16	2 1/16	3 1/8	1 3/8	1 1/4	11 3/4

All dimensions are in inches.

