



PRODUCT CATALOG

Aluminum and Copper Button Stops (Crimped Assemblies)

- ▶ Made with either 99% pure copper or high-quality aluminum alloys
- ▶ Economical terminations for non-critical applications
- ▶ Heat-treated to offer maximum cold-forming properties and long service life
- ▶ [View Dimensions Chart](#)



Choose from a wide range of button stops made with either 99% pure copper or high-quality aluminum alloys. All are economical terminations for your non-critical applications. Each has been heat-treated to offer maximum cold-forming properties and long service life.

Aluminum and Copper Button Stops Dimensions Chart (Inches)

Copper Button Stops				SW-746 Aluminum Button Stops			
Dash no.	Rope Dia.	A _s	Approx. C _s	Dash no.	Rope Dia.	A _s	Approx. C _s
101	1/32	0.115	1/4	201	1/16	0.187	1/4
151	3/64	0.155	1/4	301	3/32	0.245	3/8
201	1/16	0.182	1/4	401	1/8	0.245	3/8
301	3/32	0.261	3/8	501	5/32	0.325	3/8
401	1/8	0.261	3/8	601	3/16	0.325	3/8
501	5/32	0.350	3/8	701	7/32	0.325	3/4
601	3/16	0.350	3/8	801	1/4	0.508	13/16
701	7/32	0.350	3/4	All dimensions are in inches.			
801	1/4	0.600	13/16				
All dimensions are in inches.							

RELATED INFORMATION

[View Tuf-Grip Assemblies Handbook](#)

MacWhyte, a WireCo WorldGroup brand, understands that results matter and we produce high quality wire rope and wire rope assemblies that perform to your exacting specifications. We employ the most experienced, talented, licensed engineers in the industry to design solutions for your most complex mechanical systems. Find out for yourself how MacWhyte wire ropes and custom assemblies prove themselves time and time again in the field. **MacWhyte: Results by Design.**

