



PRODUCT CATALOG

Button Ferrule SW-705

- ▶ Excellent as a drum attachment device
- ▶ Button Ferrules develop the minimum breaking force of wire rope
- ▶ Apply at any position along an assembly to serve many functions
- ▶ Equivalent to SA157 Series
- ▶ [View Dimensions Chart](#)




The standard button material is carbon steel, but can be ordered as stainless steel if desired. Measure the length using maximum dimensions (from outside end of the ferrule).

You can specify a custom design with a different button length or finish diameter, but please send a sketch of the assembly when you order. Keep in mind that this may reduce the assembly's rated capacity.

Dimensions for Button Ferrule SW-705

Dash No.	Rope Dia.	As	Approx. Bs
3	3/32	5/16	1/2
4	1/8	3/8	5/8
5	5/32	7/16	3/4
6	3/16	1/2	7/8
7	7/32	9/16	1
8	1/4	5/8	1 1/8
9	9/32	11/16	1 3/8
10	5/16	3/4	1 1/2
12	3/8	7/8	1 3/4
14	7/16	1	2
16	1/2	1 1/8	2 3/8
18	0.5625	1.25	2.625
20	5/8	1 3/8	2 7/8
24	3/4	1 9/16	3 1/2
28	7/8	1 3/4	4 1/8
32	1	2	4 3/4
36	1 1/8	2 1/4	5 1/4
40	1 1/4	2 1/2	5 7/8
44	1 3/8	2 3/4	6 1/2
48	1 1/2	3	7 1/8

All dimensions are in inches.



RELATED INFORMATION

[View Tuf-Grip Assemblies Handbook](#)

MacWhyte, a WireCo WorldGroup brand, understands that results matter and we produce high quality wire rope and wire rope assemblies that perform to your exacting specifications. We employ the most experienced, talented, licensed engineers in the industry to design solutions for your most complex mechanical systems. Find out for yourself how MacWhyte wire ropes and custom assemblies prove themselves time and time again in the field. **MacWhyte: Results by Design.**