

OPEN SOCKET SW-710

Designed to complement each other. Built with one-piece, drop-forged steel, these TUF-GRIP sockets are rugged and compact. You can use these sockets anywhere you use zinc-poured open and closed sockets, unless your critical dimensions dictate otherwise.

EQUIVALENT TO
SA163 SERIES

Dimensions for Open Socket

Dash No.	Rope Dia.	C	D	E	F	P	A _S	X	Afterswage L _S
8	1/4	11/16	3/8	1 1/2	1 3/8	0.69	0.46	3/4	4 7/16
10	5/16	13/16	1/2	1 11/16	1 5/8	0.81	0.71	15/16	5 15/16
12	3/8	13/16	1/2	1 11/16	1 5/8	0.81	0.71	15/16	5 15/16
14	7/16	1	9/16	1 15/16	2	1.00	0.91	1 1/8	7 7/16
16	1/2	1	9/16	1 15/16	2	1.00	0.91	1 1/8	7 7/16
18	9/16	1 1/4	11/16	2 3/16	2 3/8	1.19	1.16	1 7/16	9
20	5/8	1 1/4	11/16	2 3/16	2 3/8	1.19	1.16	1 7/16	9
24	3/4	1 1/2	3/4	2 11/16	2 3/4	1.38	1.42	1 5/8	11 1/8
28	7/8	1 3/4	15/16	3 3/16	3 1/8	1.63	1.55	1 3/4	12 15/16
32	1	2	1 1/16	3 11/16	3 11/16	2.00	1.80	2 1/16	14 7/8
36	1 1/8	2 1/4	1 3/16	4 3/16	4 1/16	2.25	2.05	2 3/8	16 5/8
40	1 1/4	2 1/2	1 1/4	4 5/8	4 1/2	2.50	2.30	2 11/16	18 5/16
44	1 3/8	2 1/2	1 7/16	5 1/4	5 1/4	2.50	2.56	3	20 1/8
48	1 1/2	3	1 5/8	5 11/16	5 1/2	2.75	2.81	3 7/16	21 15/16
56	1 3/4	3 1/2	2 1/16	6 11/16	6 1/4	3.50	3.06	3 11/16	25 1/2
64	2	4	1 13/16	8 3/16	7 13/16	3.75	3.56	4 3/8	29 11/16

All dimensions are in inches.

