


PRODUCT CATALOG

Wirelon

- ▶ Resists corrosion
- ▶ Improves fatigue life
- ▶ Eliminates cable burns
- ▶ Extends service life



MacWhyte is the industry leader for coated can conveyor wire rope. Since its inception in 1960, Wirelon has proven its superiority in major food canning and can manufacturing operations. MacWhyte is now the nation's largest producer of nylon coated can conveyor rope.

Wirelon with Nylon 11 Coating is recommended for continuous exposure to temperatures below 250° F. Wirelon can be furnished in any standard size needed to fit a particular installation. Available on standard reels or in prespliced and recoated loops, it is designed to replace uncoated wire rope of the same nominal outside diameter with a minimum of preparation.

Dimensions, Minimum Breaking Forces and Weights for Wirelon

Class Core Rope Dia. Inches	Nominal Outside Dia. Inches	Minimum Breaking Force	Approx. Wt./100ft.
7x7			
3/64	1/16	270	.46
1/16	3/32	480	1.0
1/16	1/8	480	1.2
3/32	1/8	920	1.9
3/32	5/32	920	2.2
3/32	3/16	920	2.7
7x19			
1/8	3/16	2,000	3.6
1/8	1/4	2,000	4.2
3/16	1/4	4,200	7.9
1/4	3/8	7,000	14.8
*5/16	3/8	9,000	18.5
6x19			
1/4	5/16	4,300	12.4
*5/16	3/8	6,680	17.6
* Stainless or Galvanized			

Recommended working load not to exceed 1/5 of minimum breaking force.

Acceptance strength is not less than 2 1/2% below the minimum breaking force listed.

RELATED INFORMATION

Product Brochure

MacWhyte, a WireCo WorldGroup brand, understands that results matter and we produce high quality wire rope and wire rope assemblies that perform to your exacting specifications. We employ the most experienced, talented, licensed engineers in the industry to design solutions for your most complex mechanical systems. Find out for yourself how MacWhyte wire ropes and custom assemblies prove themselves time and time again in the field. **MacWhyte: Results by Design.**